



Product Datasheet

Part Code: STATIC-IPC-5MP-VF3611A

IP66 - 5MP HD Static IP Camera

Key Features

- 5 Mega Pixel IP Camera
- 3.6~11mm DC Iris Megapixel Lens
- Software controlled motorized IR cut filter
- 5-Axis mounting options including: tripod/wall and pole
- Tripod mounting includes Peli-case and WIFI options
- IP66 (International Protection Rating)
- Full HD 1080p resolution
- H.264, H265 & MJPEG video streaming
- ONVIF and RTSP compliant



Specifications

Camera	Image Sensor	1/2.7
	Max. Resolution	2506(H) x 1440(V) 5 Mega Pixels
	Min. Illustration	Color : 0.15 Lux at 50IRE / 30FPS B/W : 0.09 Lux, at 50IRE / 30FPS
	IR LED	ULTRA x 2PCS & NORMAL x 36PCS
	LENS	3.6~11mm DC Iris Mega Pixel Lens
	Electronic Shutter Speed	Automatic: Min. 1/135,000 sec ~ Max. 1/60 sec Manual: Min. 1/10,000 sec ~ Max. 1/10 sec
	Auto Exposure Mode	Automatic (Priority: Frame rate/Low noise), Manual
Mounting options	White Balance	ATW-Indoor/Outdoor, Shade, Clear sky, Fluorescent light, Light bulb, Flame, Manual
	Quick Deployment	Collapsable Tripod
Network	Static Deployment	Fixed installation using a Wall bracket or a Pole-mount adaptor bracket
	Video Compression	H.265/H.264/MJPEG
Network	Video Resolution	Main stream: 2560*1920 / 2560*1440/2304*1296 / 1920*1080/1280*720 Sub stream 1: 448P(800*488),704*576 ,640*360 , 352*288 Sub stream 2: 640*360 , 352*288
	Video Frame Rate	15fps 50HZ, 15fps 60HZ
	Video Streaming	Tripl Stream (Stream1,2,3) RTP/RTSP, UnicastRTP, Multicast RTP
	Protocols	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Search(Support P6S IP camera, DVR, NVS and etc.)
	Max. User Connection	4 Users
	SDK Support	API, ONVIF V2.4
	Ethernet Tx/Rx	RJ-45(10/100Base-T)
	Operating Humidity	0~90% (non-condensing)
	Operating Temperature	-0°C ~ +50°C
	Input Voltage	DC12V / PoE-802.3 af (option at point of order)
	Power Consumption	650mA(MAX)